

Date Prepared: 6/1/15

Safety Data Sheet

SDS-2461-ALL COLORS, Rev 0

Supersedes: MS-2461-ALL COLORS , dated 1/3/15

SECTION 1. Identification of the substance / mixture and of the company SILICA FILLED EPOXY MOLDING COMPOUND PRODUCT IDENTIFIER: FARBOSET[®] 2461 All Colors Trade Name: Chemical Name: Mixture CAS No.: None Assigned Intended Product Use: Compound used for thermoset molding Restrictions on use: None known NAME. ADDRESS. AND TELEPHONE OF MANUFACTURER Cosmic Plastics Inc. 28410 Industry Drive, Valencia CA 91355 (661) 257-3274 Fax (661) 257-3345 Homepage: www.cosmicplastics.com customerservice@cosmicplastics.com Email: **Emergency Phone Number:** SECTION 2. HAZARDS IDENTIFICATION Classification of the substance or mixture **GHS-US classification: Possible Irritant** Label Elements **GHS-US** labeling Hazard Pictograms (GHS-US) Signal word Warning Hazard statements (GHS-US): Skin Sens. 1: H316 May cause mild skin irritation. Eye Irritation: H320 May cause eye irritation. Respiratory: H335 May cause respiratory irritation EMERGENCY OVERVIEW: This product is a solid, powder compound in various colors with little to no odor. Health Hazard: This product may cause mild irritation to nose, throat, lungs or skin. Possible mild mechanical irritation to eyes. Ingestion may cause irritation of the mouth, throat and gastrointestinal tract. Flammability Hazards: This product is not flammable. Reactivity Hazards: This material does not react with water. Environmental Hazards: This material is not biodegradable. Long-term adverse effects in aquatic environments has not been determined. Emergency Considerations: Emergency responders must wear the proper personal protective equipment (and have appropriate fire suppression equipment) suitable for the situation to which they are responding.

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

Product-type:	This product is a mixture.	
<u>Components</u>	CAS Numbers	Percent
Mixed silicates as calcium silicate	1344-95-2	60-70%
Epoxy / Phenolic Resins	Trade Secret	20-30%
Brominated Resin	Trade Secret	1-5%
Antimony Oxide	1309-64-4	<1% max
Carbon black	1333-86-4	< 1%

These are typical compositions and may vary among products. A certificate of analysis is available.

SECTION 4. FIRST AID MEASURES

General Informa	tion: Change contaminated clothing.
Inhalation:	Remove victim to fresh air. If breathing is difficult, give oxygen. If not breathing, administer artificial respiration. Get medical attention.
Eye Contact:	Flush with running water for at least 15 minutes. Do not scrub. Get medical attention if irritation persists.
Skin Contact:	Wipe excess material from skin and wash with soap and water. Get medical attention if irritation persists. Wash clothing before reuse. Get medical attention if irritation occurs.
Ingestion:	If swallowed, dilute with large amounts of water or milk. DO NOT INDUCE VOMITING. Consult physician if unusual reaction is noted. Never give fluids or induce vomiting if the victim is unconscious or having convulsions.
Indication of any	immediate medical attention and special treatment needed. Treat symptomatically

Indication of any immediate medical attention and special treatment needed: Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Extinguishing Media: Special Fire Fighting Procedures:	Dry Chemical, Water Spray (Fog), Foam, Carbon Dioxide Some component materials may thermally decompose or burn emitting toxic fumes and smoke including carbon dioxide and carbon monoxide. Fire fighters should wear full protective gear including eye protection and self- contained breathing apparatus (SCBA). Do not release runoff from fire control methods to sewers or waterways.
Flash Point (⁰ F) and Method:	N.A.
Flammable Limits in air (volume %):	Lower (LEL): N/A Upper (UEL): N/A
Autoignition Temperature, ⁰ F:	N.A.
Unusual Fire and Explosion Hazards:	None.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

	Use with local exhaust to control dust formations
	Ensure adequate ventilation
	Wear personal protective equipment (see section 8) when responding to spills.
Environmental Precautions:	Do not discharge into the drains/surface waters/groundwater.
Spills / Leaks:	Sweep or vacuum spills into appropriate containers for disposal. This material is not
	regulated under RCRA or CERLA ("Superfund")
Regulatory Requirements:	Follow applicable OSHA (29 CFR 1910.120), state or local regulations.

SECTION 7. HANDLING AND STORAGE

Precautions for s	afe handling	Provide appropriate exhaust ventilation at places where dust can be generated. Wear an approved dust respirator and eye protection (goggles, safety glasses). Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.
Conditions for sa	f <u>e storage</u>	Store in closed, properly labeled containers in a dry location at 7°C/ 45° F or below. Do not freeze. Do not transfer to unmarked containers.
Shelf life:	Use within 6 mo	nths.
<u>Labeling</u>	D.O.T.: No spe	cial labels are required.

SECTION 8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Chemic	<u>eters</u>	Evenenue linite in Air
	cal Names	Exposure Limits in Air ACGIH TLV TWA OSHA PEL
Mixed silicates as	s calcium silicate	10 10 mg/m ³ (Note 4)
Epoxy / Phenolic		N/E N/E
Brominated Resi		N/E N/E
Antimony trioxid	le	0.5 0.5 mg/m ³ Sb
Carbon black		3.5 3.5 mg/m ³ respirable
Exposure Conti	rols:	
Approp	priate engineering co	ntrols: Ensure all national/local regulations are observed. General and/or local exhaust
		ventilation to control airborne dust levels below exposure limits.
<u>Biologi</u>	ical Exposure Limit:	N/A
Personal Prote	ctive Equipment:	
Respira	ators:	Recommended that users wear NIOSH/MHSA approved disposable respirators designed for
		nuisance-type dusts in accordance with the OSHA respirator regulation 29CFR 1910.134.
Eye Pro	otection:	Wear appropriate protective glasses or chemical safety goggles as described by OSHA's eye
		and face protection regulations 29 DFR 1910.133. Have eyewash facilities readily available.
Skin Pr	rotection:	Wear appropriate protective gloves to prevent skin exposure. Wash with mild soap and water
		after handling.
Clothin	•	Wear appropriate protective clothing to prevent skin exposure. Wash clothing after use.
	c overexposure effect	
workp	practices:	Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using
		toilet facilities. Promptly remove soiled clothing and wash thoroughly before reuse. Shower
		after work using plenty of soap and water.
Potential Hea		Inhalation insection skin and eve contact
Primar	y Routes of Entry:	Inhalation, ingestion, skin and eye contact
Primar Acute I	y Routes of Entry: Inhalation:	Dust can cause temporary upper respiratory (nose / throat) irritation and sensitization.
Primar Acute I	y Routes of Entry:	Dust can cause temporary upper respiratory (nose / throat) irritation and sensitization. Crystalline silica (quartz) is listed by IARC as a Group 1 carcinogenic agent in animals and
Primar Acute I	y Routes of Entry: Inhalation:	Dust can cause temporary upper respiratory (nose / throat) irritation and sensitization. Crystalline silica (quartz) is listed by IARC as a Group 1 carcinogenic agent in animals and humans. Repeated or prolonged dust inhalation can cause lung involvement such as
Primar Acute I	y Routes of Entry: Inhalation:	Dust can cause temporary upper respiratory (nose / throat) irritation and sensitization. Crystalline silica (quartz) is listed by IARC as a Group 1 carcinogenic agent in animals and humans. Repeated or prolonged dust inhalation can cause lung involvement such as pneumoconiosis or silicosis, resulting in shortness of breath, cough, difficulty in breathing and
Primar Acute I	y Routes of Entry: Inhalation:	Dust can cause temporary upper respiratory (nose / throat) irritation and sensitization. Crystalline silica (quartz) is listed by IARC as a Group 1 carcinogenic agent in animals and humans. Repeated or prolonged dust inhalation can cause lung involvement such as pneumoconiosis or silicosis, resulting in shortness of breath, cough, difficulty in breathing and lung pain. Carbon black is listed by IARC as a Class 2B potential human cancer-causing agent
Primar Acute I	y Routes of Entry: Inhalation:	Dust can cause temporary upper respiratory (nose / throat) irritation and sensitization. Crystalline silica (quartz) is listed by IARC as a Group 1 carcinogenic agent in animals and humans. Repeated or prolonged dust inhalation can cause lung involvement such as pneumoconiosis or silicosis, resulting in shortness of breath, cough, difficulty in breathing and lung pain. Carbon black is listed by IARC as a Class 2B potential human cancer-causing agent based on laboratory animal studies. Antimony oxide can lead to lung and liver damage, and
Primar Acute I Chronie	y Routes of Entry: Inhalation: c Inhalation:	Dust can cause temporary upper respiratory (nose / throat) irritation and sensitization. Crystalline silica (quartz) is listed by IARC as a Group 1 carcinogenic agent in animals and humans. Repeated or prolonged dust inhalation can cause lung involvement such as pneumoconiosis or silicosis, resulting in shortness of breath, cough, difficulty in breathing and lung pain. Carbon black is listed by IARC as a Class 2B potential human cancer-causing agent based on laboratory animal studies. Antimony oxide can lead to lung and liver damage, and changes in blood chemistry.
Primar Acute I Chronie Acute S	y Routes of Entry: Inhalation: c Inhalation:	Dust can cause temporary upper respiratory (nose / throat) irritation and sensitization. Crystalline silica (quartz) is listed by IARC as a Group 1 carcinogenic agent in animals and humans. Repeated or prolonged dust inhalation can cause lung involvement such as pneumoconiosis or silicosis, resulting in shortness of breath, cough, difficulty in breathing and lung pain. Carbon black is listed by IARC as a Class 2B potential human cancer-causing agent based on laboratory animal studies. Antimony oxide can lead to lung and liver damage, and
Primar Acute I Chronic Acute S Chronic	y Routes of Entry: Inhalation: c Inhalation: Skin Contact and Sens	Dust can cause temporary upper respiratory (nose / throat) irritation and sensitization. Crystalline silica (quartz) is listed by IARC as a Group 1 carcinogenic agent in animals and humans. Repeated or prolonged dust inhalation can cause lung involvement such as pneumoconiosis or silicosis, resulting in shortness of breath, cough, difficulty in breathing and lung pain. Carbon black is listed by IARC as a Class 2B potential human cancer-causing agent based on laboratory animal studies. Antimony oxide can lead to lung and liver damage, and changes in blood chemistry. Sitization: Temporary redness, skin irritation and itching through mechanical abrasion.
Primar Acute I Chronic Acute S Chronic Skin Ab	y Routes of Entry: Inhalation: c Inhalation: Skin Contact and Sens c Skin Contact:	Dust can cause temporary upper respiratory (nose / throat) irritation and sensitization. Crystalline silica (quartz) is listed by IARC as a Group 1 carcinogenic agent in animals and humans. Repeated or prolonged dust inhalation can cause lung involvement such as pneumoconiosis or silicosis, resulting in shortness of breath, cough, difficulty in breathing and lung pain. Carbon black is listed by IARC as a Class 2B potential human cancer-causing agent based on laboratory animal studies. Antimony oxide can lead to lung and liver damage, and changes in blood chemistry. Sitization: Temporary redness, skin irritation and itching through mechanical abrasion. Not known, none observed to date.
Primar Acute I Chronid Acute S Chronid Skin Ak Acute I	y Routes of Entry: Inhalation: c Inhalation: Skin Contact and Sens c Skin Contact: bsorption:	Dust can cause temporary upper respiratory (nose / throat) irritation and sensitization. Crystalline silica (quartz) is listed by IARC as a Group 1 carcinogenic agent in animals and humans. Repeated or prolonged dust inhalation can cause lung involvement such as pneumoconiosis or silicosis, resulting in shortness of breath, cough, difficulty in breathing and lung pain. Carbon black is listed by IARC as a Class 2B potential human cancer-causing agent based on laboratory animal studies. Antimony oxide can lead to lung and liver damage, and changes in blood chemistry. Sitization: Temporary redness, skin irritation and itching through mechanical abrasion. Not known, none observed to date. Occasional temporary redness, skin irritation and itching.
Primar Acute I Chronic Skin Ak Acute I Chronic	y Routes of Entry: Inhalation: c Inhalation: Skin Contact and Sens c Skin Contact: bsorption: Ingestion:	Dust can cause temporary upper respiratory (nose / throat) irritation and sensitization. Crystalline silica (quartz) is listed by IARC as a Group 1 carcinogenic agent in animals and humans. Repeated or prolonged dust inhalation can cause lung involvement such as pneumoconiosis or silicosis, resulting in shortness of breath, cough, difficulty in breathing and lung pain. Carbon black is listed by IARC as a Class 2B potential human cancer-causing agent based on laboratory animal studies. Antimony oxide can lead to lung and liver damage, and changes in blood chemistry. Sitization: Temporary redness, skin irritation and itching through mechanical abrasion. Not known, none observed to date. Occasional temporary redness, skin irritation and itching. Contact physician if unusual reaction is noted.
Primar Acute I Chronic Skin Ak Acute I Chronic Acute I Chronic Acute I	y Routes of Entry: Inhalation: c Inhalation: Skin Contact and Sens c Skin Contact: bsorption: Ingestion: c Ingestion: c Ingestion: Eye Contact: c Eye Contact:	Dust can cause temporary upper respiratory (nose / throat) irritation and sensitization. Crystalline silica (quartz) is listed by IARC as a Group 1 carcinogenic agent in animals and humans. Repeated or prolonged dust inhalation can cause lung involvement such as pneumoconiosis or silicosis, resulting in shortness of breath, cough, difficulty in breathing and lung pain. Carbon black is listed by IARC as a Class 2B potential human cancer-causing agent based on laboratory animal studies. Antimony oxide can lead to lung and liver damage, and changes in blood chemistry. Sitization: Temporary redness, skin irritation and itching through mechanical abrasion. Not known, none observed to date. Occasional temporary redness, skin irritation and itching. Contact physician if unusual reaction is noted. None known. Temporary eye redness and irritation. Not known, none observed to date.
Primar Acute I Chronic Skin Ak Acute I Chronic Acute I Chronic Acute I	y Routes of Entry: Inhalation: c Inhalation: Skin Contact and Sens c Skin Contact: bsorption: Ingestion: c Ingestion: Eye Contact:	Dust can cause temporary upper respiratory (nose / throat) irritation and sensitization. Crystalline silica (quartz) is listed by IARC as a Group 1 carcinogenic agent in animals and humans. Repeated or prolonged dust inhalation can cause lung involvement such as pneumoconiosis or silicosis, resulting in shortness of breath, cough, difficulty in breathing and lung pain. Carbon black is listed by IARC as a Class 2B potential human cancer-causing agent based on laboratory animal studies. Antimony oxide can lead to lung and liver damage, and changes in blood chemistry. Sitization: Temporary redness, skin irritation and itching through mechanical abrasion. Not known, none observed to date. Occasional temporary redness, skin irritation and itching. Contact physician if unusual reaction is noted. None known. Temporary eye redness and irritation. Not known, none observed to date. May Be Aggravated:
Primar Acute I Chronic Skin Ak Acute I Chronic Acute I Chronic Acute I	y Routes of Entry: Inhalation: c Inhalation: Skin Contact and Sens c Skin Contact: bsorption: Ingestion: c Ingestion: c Ingestion: Eye Contact: c Eye Contact:	Dust can cause temporary upper respiratory (nose / throat) irritation and sensitization. Crystalline silica (quartz) is listed by IARC as a Group 1 carcinogenic agent in animals and humans. Repeated or prolonged dust inhalation can cause lung involvement such as pneumoconiosis or silicosis, resulting in shortness of breath, cough, difficulty in breathing and lung pain. Carbon black is listed by IARC as a Class 2B potential human cancer-causing agent based on laboratory animal studies. Antimony oxide can lead to lung and liver damage, and changes in blood chemistry. Sitization: Temporary redness, skin irritation and itching through mechanical abrasion. Not known, none observed to date. Occasional temporary redness, skin irritation and itching. Contact physician if unusual reaction is noted. None known. Temporary eye redness and irritation. Not known, none observed to date. May Be Aggravated: Pre-existing conditions which may be aggravated by mechanical irritants upon inhalation or
Primar Acute I Chronic Skin Ak Acute I Chronic Acute I Chronic Medica	y Routes of Entry: Inhalation: c Inhalation: Skin Contact and Sens c Skin Contact: bsorption: Ingestion: c Ingestion: c Ingestion: Eye Contact: c Eye Contact:	Dust can cause temporary upper respiratory (nose / throat) irritation and sensitization. Crystalline silica (quartz) is listed by IARC as a Group 1 carcinogenic agent in animals and humans. Repeated or prolonged dust inhalation can cause lung involvement such as pneumoconiosis or silicosis, resulting in shortness of breath, cough, difficulty in breathing and lung pain. Carbon black is listed by IARC as a Class 2B potential human cancer-causing agent based on laboratory animal studies. Antimony oxide can lead to lung and liver damage, and changes in blood chemistry. Sitization: Temporary redness, skin irritation and itching through mechanical abrasion. Not known, none observed to date. Occasional temporary redness, skin irritation and itching. Contact physician if unusual reaction is noted. None known. Temporary eye redness and irritation. Not known, none observed to date. May Be Aggravated:

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical Form:	Solid granules	
Appearance:	Granular	Odor: Mild Odor threshold: Not determined
Property	Values	Remarks *Method
pH-Value:	Not determined	
Boiling Point:	Not applicable	
Change in condition		
Melting point:	Not applicable	
Boiling point:	Not applicable	
Specific Gravity @15°C (59°F	0.90 (water = 1.00)	
Decomposition Temperature	: >300°C/572°F	
Flash Point:	None	
Auto-ignition Temperature:	No information available	
Explosive Properties:	N/A	
Water Solubility:	Insoluble in water.	

SECTION 10. STABILITY AND REACTIVITY

Stability:	Stable under recommended storage conditions.
Reactivity:	Not reactive under normal conditions.
Corrosive properties:	Not corrosive
Reactivity with water:	Not reactive with water.
Conditions to avoid:	Open Fire, and strong oxidizing agents such as chlorates, bromates and nitrates.
Hazardous polymerization:	Will not occur.

SECTION 11. TOXICOLOGICAL INFORMATION

Inhalation:	Nuisance dust. May cause irritation through mechanical irritation.
Eye Contact:	Nuisance dust. May cause irritation through mechanical irritation.
Skin Contact:	Nuisance dust. May cause irritation through mechanical irritation.
Ingestion:	No Data Available
Acute Toxicology:	No Data Available.
Chronic (Long-term) Effects:	: No Data Available.
Carcinogenicity:	This product is considered as carcinogenic by OSHA, IARC, NTP or ACGIH.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity:	No Data Available
Mobility in soil:	No Data Available
Biodegradabiltiy:	Not biodegradable
Other information:	Avoid release to the environment

SECTION 13. DISPOSAL CONSIDERATIONS

This product is not considered hazardous as defined by CERCLA/RCRA (40 CFR Part 261). Material is not recyclable. Dispose of in compliance with Federal, State and local regulations.

SECTION 14. TRANSPORT INFORMATION

UN – number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not classified as dangerous goods under Department of Transportation regulations:
	(49 CFR 172.101) for road, rail, sea or air transport.
National Motor Freight Class	sification (NMFC): 156200, Class 60
D.O.T. Regulation:	Not regulated.
Export Schedule B Number:	3907.30.000 Resins Polyester, Unsaturated, Including Allyl Resins

SECTION 15. REGULATORY INFORMATION

OSHA Hazard Communication Rule, 29 CFR 1910.1200: This product is not classified a hazardous chemical.

Toxic Substance Control Act:

This product is not subject to any legal reporting requirements under this act.

Emergency Planning and Community Right-To-Know Acts:

This product is not considered as hazardous or toxic under Federal SARA, Title III or California Prop 65 definitions. **CERCLA/Superfund**, **40 CFR 117, 302**: This product contains no Reportable Quantity (RQ) substances.

SECTION 16. OTHER INFORMATION

Legend:

 Identification:
 SDS-2461-ALL COLORS

 Issue Date:
 6/1/15

 Indication of changes:
 Most recent revisions are noted by the bold, double bars in the left-hand margin throughout the document.

Other Information:

This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

	<u>Health</u>	<u>Fire</u>	Reactivity	Personal Protection
NFPA Rating:	1	1	0	
HMIS Rating:	1	1	0	E
Degree of Hazard				
0-Minimal	1-Slight	2-Moderate	3-Serious (High)	4-Severe (Extreme) *Chronic

PPE Codes (NPCA-HMIS):

A – Glasses	G – Gloves
B – Glasses, Gloves	H – Goggles, Gloves, Apron, Vapor Respirator
C – Glasses, Gloves, Apron	I – Glasses, Gloves, Dust/Vapor Respirator
D – Faceshield, Gloves, Apron	J – Goggles, Gloves, Apron, Dust/Vapor Respirator
E – Glasses, Gloves, Dustmask	K – Supplied Air, Gloves, Apron, Dust/Vapor Respirator
F – Glasses, Gloves, Apron, Dust Respirator	

Disclaimer

The information above is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. However, we make no warranty of merchantability or other warranty, express or implied, with respect to such information and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. Cosmic Plastics, Inc. will assume no liability in connection with any uses of this information. Nor will Cosmic Plastics, Inc. be responsible for any claims, losses, or damages of any third parties, or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if the company has been advised of the possibility of such damages.